



The Clear Choice in Water Treatment

Scaltrol Product Specifications

ACTIVE INGREDIENTS: Proprietary Blended Sequestrant, NSF60 Certified

SPECIFICATIONS	SC-50	SC-100	HSC-50	HSC-100	SC-500
Cartridge Capacity	50,000 gallons	100,000 gallons	50,000 gallons	100,000 gallons	500,000 Gallons
Water Flow	Up to 10 gpm	Up to 10 gpm	Up to 10 gpm	Up to 10 gpm	Up to 25 gpm
Max. Pressure Head & Sump	55 psi	55 psi	200 psi	200 psi	100 psi
Max. Temperature Head & Sump	100° F (38° C)	100° F (38° C)	200° F (93° C)	200° F (93° C)	150°F (66°C)

DIMENSIONAL DATA	SC-50	SC-100	HSC-50	HSC-100	SC-500
Hanger Bracket - Width	5"	5"	5"	5"	4.5"
Hanger Bracket - Depth	5-3/4"	5-3/4"	5-3/4"	5-3/4"	7-3/4"
Hanger Bracket - Height	2-1/2"	2-1/2"	2-1/2"	2-1/2"	5-1/2"
Sump & Head without Bracket - Height	7-3/8"	12"	7-3/8"	12"	13-1/2"
Sump & Head with Hanger Bracket - Height	10"	15"	10"	15"	19"
Width of Head - Inlet to Outlet	6"	5"	5"	5"	7-3/16"
Inlet/Outlet (Threaded Female)	3/4" NPT	3/4" NPT	3/4" NPT	3/4" NPT	1-1/2" NPT
Maximum Diameter of Head & Sump	4-5/8"	4-5/8"	4-5/8"	4-5/8"	7-1/8"
Complete Unit with Cartridge - Weight	4 lbs 2.5 oz	6 lbs 8 oz	4 lbs 2.5 oz	6 lbs 8 oz	16 lbs 9.6 oz
Complete Unit without Cartridge - Weight	2 lbs 9.2 oz	3 lbs 4 oz	2 lbs 9.2 oz	3 lbs 4 oz	NA
Replacement Cartridge - Weight	1 lb 8.5 oz	3 lbs 4 oz	1 lb 8.5 oz	3 lbs 4 oz	12.6 lbs

NOTE: Refer to the Scaltrol website for installation diagrams: www.scaltrolinc.com.

*Scaltrol Inc. • 2410 Satellite Blvd., Suite M • Buford, Georgia 30518
 Mailing address: P.O. Box 3288 • Suwanee, Georgia 30024
 Phone: 800-868-0629 • Fax: 877-769-2751 • Scaltrolinc.com*