



*The Clear Choice in Water Treatment*

## Scaltrol Product Specifications

**ACTIVE INGREDIENTS: Proprietary Blended Sequestrant, NSF60 Certified**

SPECIFICATIONS	SC-50	SC-100	HSC-50	HSC-100
Cartridge Capacity	50,000 gallons	100,000 gallons	50,000 gallons	100,000 gallons
Water Flow	Up to 10 gpm	Up to 10 gpm	Up to 10 gpm	Up to 10 gpm
Max. Pressure Head & Sump	55 psi	55 psi	200 psi	200 psi
Max. Temperature Head & Sump	120° F (49° C)	120° F (49° C)	200° F (93° C)	200° F (93° C)

DIMENSIONAL DATA	SC-50	SC-100	HSC-50	HSC-100
Hanger Bracket - Width	5"	5"	5"	5"
Hanger Bracket - Depth	5-3/4"	5-3/4"	5-3/4"	5-3/4"
Hanger Bracket - Height	2-1/2"	2-1/2"	2-1/2"	2-1/2"
Sump & Head without Bracket - Height	7-3/8"	12"	7-3/8"	12"
Sump & Head with Hanger Bracket - Height	10"	15"	10"	15"
Width of Head - Inlet to Outlet	6"	5"	5"	5"
Inlet/Outlet (Threaded Female)	3/4" NPT	3/4" NPT	3/4" NPT	3/4" NPT
Maximum Diameter of Head & Sump	4-5/8"	4-5/8"	4-5/8"	4-5/8"
Complete Unit with Cartridge - Weight	4 lbs 2.5 oz	6 lbs 8 oz	4 lbs 2.5 oz	6 lbs 8 oz
Complete Unit without Cartridge - Weight	2 lbs 9.2 oz	3 lbs 4 oz	2 lbs 9.2 oz	3 lbs 4 oz
Replacement Cartridge - Weight	1 lb 8.5 oz	3 lbs 4 oz	1 lb 8.5 oz	3 lbs 4 oz

**NOTE: Refer to the Scaltrol website for installation diagrams: [www.scaltrolinc.com](http://www.scaltrolinc.com).**

*Scaltrol Inc. • 2410 Satellite Blvd., Suite M • Buford, Georgia 30518  
Mailing address: P.O. Box 3288 • Suwanee, Georgia 30024  
Phone: 800-868-0629 ext. 201 • Fax: 877-769-2751 • [Scaltrolinc.com](http://Scaltrolinc.com)*